


MOBILE /MANUFACTURED HOMES APPLICATION REQUIREMENTS

- Copy of Approved Development Permit
- Copy of New Home Buyer Protection Act Registration
(If built after February 1, 2014)
- Copy of Construction Drawings and/or Floor Plans
- Copy of Site Plan



CERTIFICATION LABELS:

CSA Label #: _____

AMA Label #: _____

Year of Manufacture: _____

Model / Serial #: _____

Please check off boxes that apply to your mobile home set up and attach this form to your building permit application.

FOUNDATION:

- | | | | |
|--------------------------|---|--------------------------|---------------|
| <input type="checkbox"/> | Concrete Piling as per CSA | <input type="checkbox"/> | Others: _____ |
| <input type="checkbox"/> | Wood Blocking as per CSA | | |
| <input type="checkbox"/> | Concrete Blocking | | |
| <input type="checkbox"/> | Engineered Screw Piling (Must be fabricated by CWB certified welder) | | |
| <input type="checkbox"/> | Building anchorage to be provided where required. | | |
| <input type="checkbox"/> | Foundation as per Part 4 or 9 of the ABC 1997 | | |
| <input type="checkbox"/> | Refer: CSA-Z240.10.1.94 | | |

DECKS/STAIR LANDINGS

- Stairs: Rise: 125mm to 200mm (5" to 8")
Run: 210mm to 355mm (8-1/4" to 14")
Tread: 235mm to 355mm (9-1/4" to 14") Others: _____
- Handrail: 800mm to 965mm height (32" to 38")
required for exterior stairs with >3 risers. Others: _____
- Guards: 900mm height (36") required for decks/landings
600-1800mm height (2' to 6') above the adjacent grade.
1070mm height (42") for decks/landing >1800mm above grade.

CRAWLSPACE:

- Clearance: 24" between grade & bot. of floor joists Others: _____
- Ventilation minimum 1ft²/50ft² of crawl space area
- Access hatch 500mm x 700mm (20"x28") minimum
- Ground shall be graded minimum 2% for proper drainage.
- Ground cover 0.1mm poly Others: _____